

# Line Thermal Printer



## WP-T810

Printing speed : 220 mm/s

Interface : RS-232C, Parallel, USB and Ethernet



Barcord POS/ECR Gas-Pos



Black

### Interface Cards



RS-232

Parallel

Ethernet

### Accessory



58 mm paper separator

### Specification

Model	WP-T810		
Printing method	Thermal line		
Printing speed	220 mm/s		
Command	ESC/POS		
Driver	Linux, Windows and OPOS		
Character structure	Alphanumeric (Font A)	Alphanumeric (Font B)	Chinese
	12 x 24	9 x 17	24 x 24
Number of columns	48 columns	64 columns	24 columns
Character size	1.5 (W) x 3.0 (H)	1.1 (W) x 2.0 (H)	3.0 (W) x 3.0 (H)
Density	203dpi		
Fonts	Multilingual code page x 12, Chinese, Japanese, Thai, Korean, Others		
Bar code	UPC-A, UPC-E, EAN13, EAN8, Code39, Code93, CODABAR, Code128, ITF, QR Code		
Detectors	Paper end, Paper near end, Cover, Printer head overheat and Cutter jam		
Paper	Single-ply thermal paper roll		
Paper roll size	79.5±0.5 (W) x 83 mm (Dia.)		
Paper thickness	0.05 ~ 0.06 mm		
Drawer output	2		
Reliability	Head	100 km or more	
	Cutter	700,000 times	
Memory	Buffer	4K bytes	
	SRAM	256K bytes	
	Flash	1M bytes (NV Image)	
Power supply	24 VDC / 2.5 A		
Interface	Built-in USB / RS-232, Parallel and Ethernet are option		
Gross weight	2.40 kg		
External dimension	150 (W) x 190 (D) x 120 (H) mm		
Temperature	Operating	0 ~ 45°C	
	Storage	-10 ~ 50°C	
Humidity	Operating	10 ~ 90 %RH	
	Storage	10 ~ 90 %RH	