



Product Features

- High-speed printing
- Removable black mark detection
- Strong reliability,
- High print quality,
- Sturdy and durable structure
- Supports continuous paper, black mark paper
- Supports automatic paper recycling

Application



ATM machine



Gas station



Vending



Charging pile



Number taking machine

product model		KP-803
Printing	Print mode	Direct Thermal
	Print width	72mm
	Print resolution	203dpi
	Print speed max.	250mm/s (Max)
Paper	Type	Thermal receipt, Black mark paper
	Width	48-82.5mm
	Roll paper diameter (O.D)	150mm
	Roll core inner diameter (Min.)	25mm
	Thickness	0.055 to 0.09mm
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24
	Code page	48
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D barcode	QR Code,PDF417
Interface	Standard	RS232+USB+LAN
Sensor	Standard	Print head temperature, Platen position detection, Cutter home position detection Auto paper feed/ Paper out, Paper near end, Black mark detection,Paper presenter
Reliability	Cutting method	Full cut
	Cutter life	1,000,000cuts
	TPH life	100km
Input Power	AC	AC100V-240V 50/60Hz
	DC	DC24V,2A
Dimensions	(WxLxHmm)	116.6 x182.1x72.6
	Weight	1.47kg
Emulation	Commands	ESC/POS
	Driver	Windows Driver,Linux Driver,OPOS Driver
Software	SDK	Windows SDK,Android SDK,Linux SDK
	Environment	Temperature
Humidity		Operating:20%RH~85%RH Storage:10%~90%RH