



■ Product Features

- Low noise, high speed printing;
- Automatic paper feeding;
- Support full/partial cut;
- Centered printing;
- Paper detection function;
- Automatically eliminate stuck cutter function;
- Compatible with various paper width adjustments.

■ Application



ATM machine



Gas station



Vending



Charging pile



Number taking machine

Product model		KP-302	
Printing	Print mode	Direct Thermal	
	Print width	76mm	
	Print resolution	203dpi	
	Print speed max.	250mm/s	
Paper	Type	Thermal receipt, Black mark paper, Thermal label	
	Width(Max)	58mm/80mm	
	Roll paper diameter (O.D)	120mm	
	Roll core inner diameter (Min.)	13mm/25mm	
	Thickness	Within 0.12mm (label)	
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24	
	Code page	48	
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93	
	2D barcode	QR Code,PDF417	
Interface	Standard	USB+RS232	
	Optional	LAN	
Sensor	Standard	Print head temperature/Platen position detection/Cutter home position /Auto paper feed/Paper taken/Paper near end/Black mark detection	
	Optional	Gap detection	
Reliability	Cutting method	Full/Partial cut	
	Cutter life	1,000,000cuts	
	TPH life	100km	
Input Power	AC	110V-220V	
	DC	DC24V,2A	
Dimensions	(WxLxHmm)	141.1x115.2x77mm	
	Weight	kg	
Emulation	Commands	ESC/POS	
	Driver	Windows Driver, Linux Driver, OPOS Driver	
Software	SDK	Windows SDK, Android SDK, Linux SDK	
	Environment	Temperature	Operating:-10°C~50°C
Humidity(No condensation)		Operating:20%RH~85%RH	Storage:10%~90%RH