



Product Features

- Low noise, high-speed printing
- Auto paper feeding, easy paper loading structure
- Support full /partial cut
- Paper taken detection function reminder
- Auto cutter jam elimination function
- Compatible with multiple paper width adjustments

Application



ATM machine



Gas station



Vending



Charging pile



Number taking machine

Product model		KP-T301	
Printing	Print mode	Direct Thermal	
	Print width	72mm	
	Print resolution	203dpi	
	Print speed max.	250mm/s	
Paper	Type	Thermal receipt	
	Width	82.5mm	
	Roll paper diameter (O.D)	150mm	
	Roll core inner diameter (Min.)	25mm	
	Thickness	0.055-0.09mm	
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24	
	Code page	48	
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93	
	2D barcode	QR Code,PDF417	
Interface	Standard	RS232+USB	
	Optional	--	
Sensor	Standard	Paper end, Paper near end, Paper taken, Black mark detection,Paper Presence	
	Optional	Anti paper jam, Anti-drag ticket	
Reliability	Cutting method	Full cut	
	Cutter life	1,000,000cuts	
	TPH life	100km	
Input Power	AC	AC100V-240V 50/60Hz	
	DC	DC24V,2A	
Dimensions	(WxLxHmm)	181.7x145.1x201.1	
	Weight	1.56kg	
Emulation	Commands	ESC/POS	
	Driver	Windows Driver, Linux Driver, OPOS Driver	
Software	SDK	Windows SDK, Android SDK, Linux SDK	
	Environment	Temperature	Operating: -10°C~50°C
Humidity(No condensation)		Operating: 20%RH~85%RH	Storage: 10%~90%RH