

BIOSTAR BP1500



Easy access M.2 SSD
for easy installation



IP64
Front Panel Protection

CPU	Intel Alder Lake-N N97
Display	15"
Resolution	1024*768, 4:3
Touch screen	15" Projected Capacitive Touch
Memory	1 x DDR4 3200Mhz SO-DIMM, up to 16 GB
OS support	WINDOWS 10 IoT / WINDOWS 11 IoT
Graphics	Intel® UHD Graphics
Display Panel	15" TFT LCD (LED backlight) / eDP
Display Port	1 x HDMI (3840 x 2160 @30Hz)
Interface	2*USB2.0; 4*USB3.0; 4*COM(RJ50); 1*HDMI; 1*Audio;1*Lan;1*RJ11
Dimension (LxWxH)	358.45 x 223.5 x 420 mm
Customer display	VFD Optional
Customer screen	9.7"/15" LCD Display(Optional)
Wi-Fi/BT/MSR	Optional
Power adaptor	100-240V/50-60HZ, AC power input,DC 12V/5A output
Net Weight	7.5KG
Operating temperature	0°C -40°C
Storage temperature	-20°C ~75°C



Vectronix System Inc. <http://www.vectronix.com.tw>

TEL:886-2-8227-3177 FAX:886-2-8227-3167

4F.-1, No.268, Liancheng Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)